

# Technical Data Sheet

## Dokumental® TS 96xx T-Shirt Marker Inks

### Permanent T-Shirt Marker Inks

#### General Information

The inks of Dokumental® TS 96xx series are pigmented inks with high light fastness. They are suitable for painting on fabrics and are permanent without ironing (laundry safe up to 60°C).

#### Suitable Surfaces

Textiles

#### Applicable Standards & Regulations on Request

#### Physical Data

Type	Colour	Viscosity at 20°C mPa s ± 0.5	Surface tension mN/m ± 2.0	pH-Value ± 1.0	Density at 20°C g/cm <sup>3</sup> ± 0.02
Dokumental® TS 9600.2	blue	4.6	41.0	8.3	1.06
Dokumental® TS 9601.2	light blue	4.6	41.0	8.3	1.07
Dokumental® TS 9602.2	pale blue	3.5	41.0	8.3	1.05
Dokumental® TS 9610.2	black	5.2	41.0	8.3	1.07
Dokumental® TS 9612.2	grey	3.6	40.4	8.3	1.06
Dokumental® TS 9620.2	red	5.2	41.5	8.3	1.06
Dokumental® TS 9622.2	rose red	4.4	40.4	8.3	1.06
Dokumental® TS 9623.2	skin	3.6	41.2	8.1	1.06
Dokumental® TS 9630.2	green	4.9	41.0	8.3	1.07
Dokumental® TS 9631.2	yellow green	5.3	41.0	8.3	1.06
Dokumental® TS 9640.2	violet	4.1	39.0	8.3	1.05
Dokumental® TS 9642.2	elder	3.6	41.0	8.3	1.05
Dokumental® TS 9650.2	brown	5.2	41.0	8.3	1.05
Dokumental® TS 9651.2	light brown	3.9	41.0	8.3	1.05
Dokumental® TS 9660.2	yellow	7.3	41.0	8.3	1.07
Dokumental® TS 9661.2	yellow orange	5.2	41.0	8.3	1.04
Dokumental® TS 9662.2	orange	4.0	41.0	8.3	1.05
Dokumental® TS 9670.2	magenta	5.4	41.0	8.3	1.05
Dokumental® TS 9671.2	light rose red	3.6	41.0	8.3	1.06
Dokumental® TS 9680.2	beige	3.8	41.0	8.3	1.05
Dokumental® TS 9681.2	yellow fluo	5.5 (± 1.0)	36.0	6.5 (± 0.5)	1.06
Dokumental® TS 9682.2	orange fluo	5.5 (± 1.0)	36.0	6.5 (± 0.5)	1.06
Dokumental® TS 9684.2	pink fluo	5.5 (± 1.0)	36.0	6.5 (± 0.5)	1.06
Dokumental® TS 9685.2	green fluo	5.5 (± 1.0)	36.0	6.5 (± 0.5)	1.06

### Permanent T-Shirt Marker Inks

#### Technical Advice

Suitable Components:

Nibs: polyester, acrylic with high porosity

Barrels, Caps and Plugs: polypropylene, polyethylene

Reservoir: polyester

It is mandatory to approve the compatibility of the ink and the components as well as the performance of the writing system.

#### Storage, Handling & Transportation

Before use of our product the filling station has to be maintained and cleaned carefully. The inks are sensitive to any kind of contamination. Cross-contamination of the inks may lead to a colour mismatch or will even lead to a defective refill or shorter shelf life.

Store our product frost protected and avoid direct sunlight. The recommended storage temperature is between 10°C and 30°C. Storage temperatures of above 30°C for several days bear the risk of a reduced shelf life of the ink.

After usage the drums have to be closed again tightly.

Markers should be stored horizontally.

The applied inks should dry over night on the fabric. Fixing by ironing from the back side (iron set on cotton or level III, for 10 - 15 seconds) will increase the permanency of the markings.

Ink-flow tests should be carried out on fabrics and not on paper.

Handling of bulk ink:

Stir well before use and stir ink during ink injection in order to avoid pigment sedimentation during filling process.

The shelf-life of the inks in originally sealed containers is 2 years.

#### Packaging

standard packaging: 20kg plastic canister (further packaging units on request)

#### Produced by

DOKUMENTAL GmbH & Co KG

Wöllnerstraße 26

D-67065 Ludwigshafen

Phone: +49(0)621/37702-200

Fax: +49(0)621/37702-391

Mail: [info@dokumental.de](mailto:info@dokumental.de)

[www.dokumental.de](http://www.dokumental.de)