Technical Data Sheet **Dokumental® LM 23xx** Paint Marker Inks



Pigmented Paint Marker Inks for valve action markers

General Information

Dokumental® LM 2399.1 provides an outstanding mirror-effect especially on smooth surfaces. The Gold and Copper exhibit a very nice glossy, shiny and metallic appearance. All inks have a high covering power and a perfect line homogeneity and are therefore the best choice for decorating purposes. The inks are formulated for valve action markers.

Suitable Surfaces

For all kind of smooth surfaces

Applicable Standards & Regulations

Unless expressly agreed, no warranty is given that all standards & regulations relevant to the Customer's intended use have been and will be complied with. To the extent that compliance with certain standards & regulations is warranted, this warranty shall only apply at the time the underlying contract is entered into. There is no guarantee that the products will continue to comply with the standards & regulations in the event of future changes. Dokumental also assumes no obligation to inform the Customer of any changes to such standards & regulations that may be relevant to the Customer.

Physical Data

Туре	Colour	Viscosity at 20°C mPa s
Dokumental® LM 2399.1	mirror silver	11.0 - 16.0
Dokumental® LM 2398	shiny gold	15.0 - 20.0
Dokumental® LM 2397	shiny copper	15.0 - 20.0

Technical Advice

Suitable Components

Use valve action markers only!

Corrosion safe ball (SS or glass) inside the barrel grants a good distribution of the pigments by shaking the marker before use.

Nibs: polyester and acrylic with high porosity.

Barrels, Caps, Plugs: polypropylene, pure aluminum

It is mandatory to approve the compatibility of the ink and the components as well as the performance of the writing system.

Storage, Handling & Transportation

Stir well before use and stir ink during ink injection in order to avoid pigment sedimentation during filling process.

Before use of our product the filling station has to be maintained and cleaned carefully. The inks are sensitive to any kind of contamination. Cross-contamination of the inks may lead to a colour mismatch or will even lead to a defective marker or shorter shelf life

Store our product frost protected and avoid direct sunlight. The recommended storage temperature is between 10°C and 30°C. Storage temperatures of above 30°C for several days bear the risk of a reduced shelf life of the ink.

Drums should be closed tightly during storage.

The shelf-life of the inks is 1 year in original sealed containers.

Horizontal storage of the markers is recommended in order to get the maximum shelf life.

CAUTION: the inks are classified as flammable liquids!

For detailed safety information refer to the respective Material Safety Data Sheets.

Packaging

standard packaging: 25kg steel drum

Produced by

DOKUMENTAL GmbH & Co KG Wöllnerstraße 26 D-67065 Ludwigshafen

Phone: +49(0)621/37702-200 Mail: info@dokumental.de

www.dokumental.de